

Auto-Trailer

Fully automatic tilt-bed, the ultimate in vehicle transporter trailers.

A stable 'four wheels-on-the-floor' chassis and a unique automatic hydraulic deck control system enable loading and unloading of driven vehicles in around 30 seconds. Unloading, as you drive off the AutoTrailer tilts to the ground.

Auto-Trailers feature the highest level of standard equipment to ensure you get the best available setup from day one. Additional security devices are also available to complement the standard in-built coupling lock.



Auto-Trailer Product codes	Load bed length	Load bed width	Gross cap. Kg	Load cap. Kg	Price	Onboard storage box	Quick change wheel chocks (pair)	Spare wheel	Head lock	Centre deck	H.D. Jockey wheel	Winch 2 gears manual	Tie-down wheel straps	5 YEAR chassis warranty
AJ-T-400	4.26m (14ft)	1.85m (6ft 1)	2,300	1,750	£ 2,425	✓	✓	✓	✓	✓	✓	✓	✓ H.D. (4)	✓
AJ-T-100	4.30m (14ft 2)	1.93m (6ft 3)	2,600	2,000	£ 2,995	✓	✓	✓	✓	✓	✓	✓	✓ H.D. (4)	✓

Overall trailer dimensions:

OVERALL LENGTH AJ-T-400	6.0m (19ft 8)
OVERALL LENGTH AJ-T-100	6.0m (19ft 8)
OVERALL WIDTH (all models)	2.30m (7ft 6)

Auto-Trailer STANDARD features

- Spare wheel / tyre fitted
- Fully automatic hydraulic operation tilt-bed with deck control system
- 4 wheel auto reverse brakes
- 155/70R12 tyres on HD 12" commercial rims
- Multi-hole deck for traction and tie-down facility
- 50mm ball coupling
- Integral tow hitch lock facility
- Ramp free loading, drive straight onto tilted trailer
- Integrated modern lighting system to full EEC directives. Rear lamps fully protected. Flexible mounted rear corner marker lamps
- Stable with low centre of gravity
- On board storage box and a complete set of 4 off HD wheel straps
- Tandem mudguards with full time door opening clearance.
- Fully hot-dip galvanised steel chassis
- 5 YEAR chassis warranty
- 3 YEAR trailer component warranty



Loading and unloading is as easy as...

1. Release bed to tilt, stand on rear of trailer, bed tilts to ground ready to drive on.
2. Drive on (or winch if recovering) and step out onto convenient mudguard.
3. Turn hydraulic deck control system release wheel, bed lowers gently into place for travel.

